

# FlashRunner Series Comparison Table

DC01388



Features	FlashRunner I Series					FlashRunner II Series	FlashRunner III Series
	FR01ENG	FR01USB	FR01LAN	FR01PRO	FR01M01		
<b>Programming Support</b>	Universal	Universal	Universal	Universal	Universal	One Manuf.	One Device
<b>Interface</b>	RS-232	USB/RS-232	LAN/RS-232	LAN/RS-232	LAN/RS-232	LAN/RS-232	RS-232
<b>ISP Sites</b>	1	1	1	1	8 (Multiplexed)	1	1
<b>ISP Connector Type</b>	Header	D-Sub	D-Sub	D-Sub	Header	D-Sub	D-Sub
<b>Power Supply</b>	9-24V DC	9-24V DC	9-24V DC	110/220V AC	9-24V DC	9-24V DC	7.5V DC
<b>SD Card (up to 2GB)</b>	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes
<b>Logs/Reports</b>	Yes	Yes	Yes	Yes	Yes	Yes	No
<b>On-Board Dynamic Memory</b>	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	-
<b>Scripts (Host Mode)</b>	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	1
<b>Scripts (Standalone Mode)</b>	32	32	32	32	32	32	1
<b>Dimensions (mm)</b>	130 x 74 x 27	130 x 74 x 27	130 x 74 x 43	360 x 210 x 45	130 x 74 x 43	130 x 74 x 43	90 x 53 x 33
<b>Real-Time Clock/Calendar</b>	Yes	Yes	Yes	Yes	Yes	Yes	No
<b>Optoisolation</b>	Yes	Yes	Yes	Yes	Yes	Yes	No